


AN: PAT 1998-171315  
TI: System for notifying user of awaiting messages and connected to door lock system has messaging device, lock system, connecting device and contacting device, and connecting device processes signals from lock system and to messaging device and also monitors lock system  
PN: EP831633-A2  
PD: 25.03.1998  
AB: The system for notifying a user of waiting messages, characterised in that it comprises a message storage device (30) , a lock system (20). A device provides information relating to waiting messages to the user in response to an activation of the lock system by the user. The device for providing information relating to messages to the user includes a central computer (40) for coordinating information and for communicating with the lock system and the message storage device. The central computer communicates with the lock system and the message storage device (30) by at least one of a wired electrical connection and a wireless connection. The wired electrical connection is at least one of a hotel telephone system, a business telephone system and a PBX.; USE - E.g. for telephone messaging system. ADVANTAGE - Has improved communication and improved security of message handling.  
PA: (SIEI ) SIEMENS BUSINESS COMMUNICATION SYSTEMS;  
(SIEI ) SIEMENS INFORMATION & COMMUNICATIONS NET;  
IN: BEYDA W J; SHAFFER S;  
FA: EP831633-A2 25.03.1998; DE69732163-E 10.02.2005;  
US5802147-A 01.09.1998; EP831633-B1 05.01.2005;  
CO: AL; AT; BE; CH; DE; DK; EP; ES; FI; FR; GB; GR; IE; IT; LI;  
LT; LU; LV; MC; NL; PT; RO; SE; SI; US;  
DR: AL; AT; BE; CH; DE; DK; ES; FI; FR; GB; GR; IE; IT; LI; LT;  
LU; LV; MC; NL; PT; RO; SE; SI;  
IC: H04M-001/64; H04M-003/50;  
MC: T01-J08C; W01-C02B7C; W01-C02D3; W01-C02G5; X25-M01;  
DC: T01; W01; X25;  
FN: 1998171315.gif  
PR: US0716116 19.09.1996;  
FP: 25.03.1998  
UP: 18.02.2005

BEST AVAILABLE COPY

BEST AVAILABLE COPY


DAMAGE



DEWEE

2003 F U L S 76

82



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 0 831 633 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:  
25.03.1998 Bulletin 1998/13

(51) Int Cl.<sup>6</sup>: H04M 3/50

(21) Application number: 97307299.4

(22) Date of filing: 19.09.1997

(84) Designated Contracting States:  
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE  
Designated Extension States:  
AL LT LV RO SI

(72) Inventors:  
• Beyda, William J.  
Cupertino, CA 95014 (US)  
• Shaffer, Shmuel  
Palo Alto, CA 94301 (US)

(30) Priority: 19.09.1996 US 716116

(74) Representative: Muir, Ian R.  
Haseltine Lake & Co.,  
Imperial House,  
15-19 Kingsway  
London WC2B 6UD (GB)

(71) Applicant: Siemens Business Communication  
Systems, Inc.  
Santa Clara, CA 95054 (US)

(54) System and method for notifying a user of waiting messages

(57) A system for notifying a user of awaiting messages is provided. This system includes a messaging device (30), a lock system (20), a connecting means (40) and a contacting means (30). Connecting means (40) processes signals from lock system (20) and to messaging device (30). Connecting means (40) also monitors lock system (20) and sends user related information to messaging device (30). Contacting means (30) automatically contacts the user with information related to the awaiting messages.




Figure 2

## Description

The invention relates to notifying a user of waiting messages, and more particularly to a system and a method for electrically connecting a messaging system with a door lock system.

Telephone messaging systems (i.e., voice mail systems) are common and readily available. Electronic door lock systems are also common. For example, many hotels employ both. While currently available messaging systems are adequate, they have several shortcomings. For example, in hotels, users must remember to check the message waiting light to see if any messages have arrived. Hotels often rely on analog telephones, so it is not uncommon for the message waiting light bulb to burn out. Therefore, if the guest does not notice the light or does not remember to check the telephone, the guest will not know if any messages have arrived.

In addition, for simplicity, hotels do not usually utilize the password feature of their messaging systems. Thus, anyone with access to a guest's room can pick up the telephone and retrieve that guest's messages. This provides for little security. It is desirable to provide an intelligent interconnection between messaging systems and door lock systems to improve the communication of awaiting messages to users and to improve the security of the messaging system.

A system for notifying a user of waiting messages in accordance with the invention is as set out in claim 1.

A method for notifying a user of waiting messages in accordance with the invention is as set out in claim 5.

According to one embodiment of the invention, a system for notifying a user of waiting messages is provided including a messaging device, a lock system, a connecting means and a contacting means. The connecting means processes signals from the lock system and to the messaging device. This connecting means also monitors the lock system and sends user related information to the messaging device. The contacting means automatically contacts the user with information related to the waiting messages.

For a better understanding of the present invention, and to show how it may be brought into effect, reference will now be made, by way of example, to the accompanying drawings, in which:

Figure 1 illustrates the basic subsystems of the present invention in a hotel environment; and  
Figure 2 illustrates a process flow chart for the present invention.

The present invention provides an apparatus and a method for connecting a messaging system with a door lock system. The messaging system can be any multimedia messaging system including telephone voice mail, video mail, electronic mail (i.e., e-mail) messages, facsimile messaging system and the like. The door lock

system can be located in various environments. For example, the already existing electronic door lock systems in hotels can be utilized, or electronic door locks can be placed in a business (or other) environment.

In one embodiment of the invention, the electronic door lock system is located in a hotel environment. Figure 1 illustrates the basic subsystems of the present invention in a hotel environment. Hotel 10 includes a lock system 20, a messaging system 30, a central computer 40 and an output 50. Messages are placed in messaging system 30 by input 60. In this example, input 60 is a telephone located outside of hotel 10. As stated above, many hotels already utilize electronic door locks. Electronic door lock system 20 is usually operated by either magnetically or mechanically encoded cards which are programmed specifically for each guest/user. These encoded cards act as hardware passwords which can open the users' multimedia messaging mailbox(es).

Many hotels use a voice mail messaging system 30. Usually, the password protection provided by that system is not utilized by the hotel because they do not want to administer the distribution and tracking of the passwords. As a result, anyone who picks up a telephone in a hotel room can access the associated voice mail messaging system. This gives access to maids, bellhops and everyone else with access to the hotel rooms. This results in inherently insecure voice mail messaging systems.

In addition to messaging system 30, a hotel may include central computer 40. Often door lock system 20 is linked to central computer 40 such that each electronic card inserted into a door is checked by central computer 40. When the check is positive, the lock is opened by a command from central computer 40. In the preferred embodiment, a guest's electronic card produces a different electronic code from other individuals' electronic codes (e.g., the maid's electronic code). Therefore, while both electronic cards can open the door, only the guest's electronic card causes central computer 40 to trigger multimedia messaging system 30.

Figure 2 illustrates a process flow chart for the present invention. At step 100, the electronic card or key is placed in the door lock. At step 110, information related to the electronic card and the door lock is sent to the central computer. When a guest inserts an electronic card into the door lock, the central computer checks the electronic card. If the check is positive, the central computer sends a signal which activates (or opens) the guest's door lock. At step 120, the central computer sends a command over, for example, a digital link to the messaging system. This command identifies the guest. Identification can be in relation to the guest's room number, the guest's mailbox number, the guest's telephone extension number or the like. The messaging system then checks to see if there are any messages for the identified guest at step 130. If there are no messages, the process ends at step 140.

If a message(s) is present, the messaging system

sends a command over, for example, a digital link to a switch to contact the guest/user at step 150. For example, a command can be sent to the hotel telephone system or a PBX (private branch exchange) such that a call is placed to the guest's room. A short delay can be inserted (e.g., 5 seconds) to allow the user to get inside the room before the telephone starts to ring. At step 160, the message(s) is played for the guest. For example, when the user answers the telephone, an automated message could begin by saying "you have N new message(s)," and then the messaging system could play the message(s) for the user. By providing this contacting feature, messaging system security, usability and administration is improved.

When a user checks into a hotel which utilizes the present system, a telephone number for changing the system options can be provided to the user. For example, the user could dial this telephone number and change the delay to a longer period of time (e.g., 30 seconds) to give the user more time to get settled in the room before the telephone started to ring. The telephone call could then connect the user to the user's message mailbox. This "option change" telephone number can also be used to avoid disturbing customers/users. The user could, if desired, change their options (by using the telephone number) to disable their automatic contacting feature.

In this arrangement, messages can only be retrieved by inserting an electronic card or key into the door. If the electronic card is lost, security is compromised, but that already occurs with the prior art system because anyone with access to a room can retrieve messages.

In another embodiment of the present invention, the electrical or mechanical locks are not connected to a central computer. In this situation, an electronic card or a key is coded at the hotel's front desk with a code including the hotel room number and the dates of the guest's stay, if applicable. The door lock is preprogrammed to accept any card or key with the correct coded room number and dates. The lock is self-contained and sometimes battery operated. Thus, this type of lock does not connect to the front desk or to a central computer. To modify this lock for the present invention, the lock is connected to a central computer via a wired or a wireless connection. For example, an electrical wire for transferring electrical signals can be used to connect each lock with the central computer, or transmitters/receivers can be located on both the door locks and the central computer for transferring wireless signals. The locks could also be designed to attach to the telephone line already in the room with wires or a wireless connection. If the telephone line is used, dual tone multi frequency (DTMF) tones or other signals can be transmitted to the messaging system to communicate the unlocking of the door with the guest's card/key. If DTMF tones are used, a special telephone number is utilized to connect the door lock to the central computer. Then,

the relevant data is sent with more DTMF tones or with any other data transmission standard (e.g., a modem standard).

Additionally, in the hotel example, if multiple users are sharing a room, each user could be checked in separately and given a different electronic card/key which refers to that user's message mailbox. When a caller specifies a guest name, messages from that caller are then directed to the appropriate guest's mailbox. Therefore, multiple guests can retrieve messages from their individual mailboxes without additional administration costs and without compromising security. Moreover, separate identifications or passwords are not needed.

In a business environment, electronic office door locks can be utilized in the same way as the hotel door locks. Again, a connection would be provided between the electronic office door locks and the business' messaging system. Many businesses already have electronic office door locks which track each employee's arrival (or other) time. These systems usually include a central computer for tracking the time. After the central computer is connected to the messaging system, the central computer can be used to implement the present invention. As set forth above, the central computer can detect when a user has entered a room. A signal is then sent to the messaging system. The messaging system checks for awaiting messages and evaluates the possibility of contacting the user.

In another embodiment, the present invention is used in a telecommuting center environment. A telecommuting center is used when multiple individuals share one office or work space. For example, several salespeople who are usually "on the road" may be able to share the same office. In the past, these salespeople could dial a code into their common telephone to identify themselves and retrieve their telephone messages. With the present invention, electronic keys can be used for identifying the salespeople and giving access to messages. After the central computer identifies the individual using the shared office, the central computer can allow the identified user to be contacted through the common telephone. For example, the identified user's telephone extension would ring on the common telephone. Optionally, the user could also utilize the electronic key when exiting the shared office to both (1) lock the door and (2) indicate that the user was vacating the area. Thus, the user's telephone extension would not ring the common telephone after the user had left the shared office. In another arrangement of this embodiment, the electronic key could work in a wireless fashion to indicate to the central computer when a user had entered and/or exited a shared office. For example, a receiver located in the shared office could receive user identification information transmitted from the electronic key and then transfer that information to the central computer. When the transmission from the electronic key ended, information could be sent to the central computer indicating that the user had left the shared office.

**Claims**

1. A system for notifying a user of waiting messages, characterised in that it comprises a message storage means (30), a lock system (20), and means for providing information relating to waiting messages to the user in response to an activation of the lock system (20) by the user. 5
2. The system for notifying a user of waiting messages as claimed in claim 1, wherein the means for providing information relating to messages to the user includes a central computer (40) for coordinating information and for communicating with the lock system (20) and the message storage means (30). 10 15
3. The system for notifying a user of waiting messages as claimed in claim 2, wherein the central computer (40) communicates with the lock system (20) and the message storage means (30) by means of at least one of a wired electrical connection and a wireless connection. 20
4. The system for notifying a user of waiting messages as claimed in claim 3, wherein the wired electrical connection is at least one of a hotel telephone system, a business telephone system and a PBX. 25
5. A method for notifying a user of waiting messages stored in a message storage means, characterised in that it comprises the steps of: 30
  - monitoring a lock system; and
  - automatically contacting the user with information related to waiting messages when it is determined that the user has activated the lock system. 35
6. The method for notifying a user of waiting messages as claimed in claim 5, further comprising the step of playing the waiting messages for the user. 40
7. The method for notifying a user of waiting messages as claimed in claim 5 or 6, further comprising the step of transmitting a first signal from the lock system to a central computer, the first signal notifying the central computer of the lock system activation and identifying the user wherein the first signal is transmitted over at least one of a wired electrical connection and a wireless connection. 45 50
8. The method for notifying a user of waiting messages as claimed in one of claims 5-7, further comprising the step of transmitting a second signal from the central computer to a message storage means, the second signal notifying the message storage means of the activation of the lock system and identifying the user, wherein the second signal is transmitted over at least one of a wired electrical connection and a wireless connection. 55
9. The system for notifying a user of waiting messages as claimed in claims 1-4, or the method for notifying a user of waiting messages as claimed in one of claims 5-8, wherein the lock system is located in at least one of a hotel, a business and a telecommuting center.
10. The system for notifying a user of waiting messages as claimed in one of claims 1-4 or 9, or the method for notifying a user of waiting messages as claimed in one of claims 5-9, wherein the message storage means is at least one of a voice mail system, a video mail system, an electronic mail system and a fax messaging system.
11. The system for notifying a user of waiting messages as claimed in one of claims 1-4, 9 or 10, or the method for notifying a user of waiting messages as claimed in one of claims 5-10, wherein the lock system is an electronic door lock.
12. The system or method for notifying a user of waiting messages as claimed in claim 11, wherein the electronic door lock includes encoded locks, each of the encoded locks being programmed for a specific user.
13. The system or method for notifying a user of waiting messages as claimed in claim 12, wherein the central computer determines when the electronic door lock is activated in response to a user input.






Figure 1





Figure 2



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 0 831 633 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
04.08.1999 Bulletin 1999/31

(51) Int Cl.<sup>6</sup>: **H04M 3/50**

(43) Date of publication A2:  
25.03.1998 Bulletin 1998/13

(21) Application number: **97307299.4**

(22) Date of filing: **19.09.1997**

(84) Designated Contracting States:  
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE**  
Designated Extension States:  
**AL LT LV RO SI**

(72) Inventors:  
• **Beyda, William J.**  
Cupertino, CA 95014 (US)  
• **Shaffer, Shmuel**  
Palo Alto, CA 94301 (US)

(30) Priority: **19.09.1996 US 716116**

(74) Representative: **Muir, Ian R.**  
Haseltine Lake & Co.,  
Imperial House,  
15-19 Kingsway  
London WC2B 6UD (GB)

(71) Applicant: **Siemens Business Communication  
Systems, Inc.**  
Santa Clara, CA 95054 (US)

(54) **System and method for notifying a user of waiting messages**

(57) A system for notifying a user of awaiting messages is provided. This system includes a messaging device (30), a lock system (20), a connecting means (40) and a contacting means (30). Connecting means (40) processes signals from lock system (20) and to messaging device (30). Connecting means (40) also monitors lock system (20) and sends user related information to messaging device (30). Contacting means (30) automatically contacts the user with information related to the awaiting messages.




Figure 2

EP 0 831 633 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 97 30 7299

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IntCl.6)
A	WO 95 18501 A (GTE LABORATORIES INC) 6 July 1995	1,5	H04M3/50
A	DE 42 21 439 A (HOTEC ELEKTROHANDELS GMBH) 5 January 1994	1,5	
A	US 5 414 759 A (ISHIKURI HIROAKI ET AL) 9 May 1995		
			TECHNICAL FIELDS SEARCHED (IntCl.6)
			H04M
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>14 June 1999</b>	Examiner <b>Vandevenne, M</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone  Y : particularly relevant if combined with another document of the same category  A : technological background  O : non-written disclosure  P : intermediate document</p> <p>T : theory or principle underlying the invention  E : earlier patent document, but published on, or after the filing date  D : document cited in the application  L : document cited for other reasons  &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 30 7299

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14-06-1999

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9518501	A	06-07-1995	NONE	
DE 4221439	A	05-01-1994	NONE	
US 5414759	A	09-05-1995	JP 3270453 A	02-12-1991
			CA 2038476 C	07-02-1995
			DE 69126806 D	21-08-1997
			EP 0448076 A	25-09-1991

EPO FORM P0159

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

BLANK PAGE

BLANK PAGE